

## Catalog No. NP-001



Neutral Displacement Needleless Valve

**Approx.  
Priming Vol.  
<0.10 mL**

**100 EA Per  
Box**

### PRODUCT FEATURES & BENEFITS:

- **NEUTRAL DISPLACEMENT NEEDLELESS VALVE**
- **NEUTRAL FLUID DISPLACEMENT AT BOTH LUER CONNECTION OR DISCONNECTION HELPS REDUCE REFLUX-RELATED OCCLUSIONS. DOES NOT REQUIRE CLINICIAN CLAMPING.**
- **DUAL SEAL DESIGN INTENDED TO DEFEND AGAINST MICROBIAL INGRESS AND PROVIDE REDUNDANT LEAK PROTECTION IN CRITICAL ARTERIAL AND HIGH PRESSURE APPLICATIONS AND DOES NOT REQUIRE CLINICIAN TO CONTROL VALVE-INDUCED REFLUX**
- **LOW PRIMING VOLUME ALLOWS FOR LOWER FLUSH VOLUMES**
- **CLEAR HOUSING FACILITATES VISUALIZATION OF ENTIRE FLUID PATH DURING PRIMING AND FLUSHING**
- **SYSTEM BACK PRESSURE – 45 PSI**
- **OPTIMAL FOR HIGH-PRESSURE APPLICATIONS. MAXIMUM PRESSURE RATING OF 330PSI**
- **MAXIMUM FLUID DISPLACEMENT (FOR DISCONNECTIONS OF MALE LUER SYRINGE) - +2 MICROLITER**
- **MATERIALS ARE COMPATIBLE WITH, BLOOD, ALCOHOL, LIPIDS, CHLORHEXIDINE, AND CHEMOTHERAPY. ALSO SAFE FOR USE IN MRI**
- **NON-DEHP AND LATEX FREE**